

BTW LED BASIC TROFFER



HARCROFT LIGHTING

Proudly Australian Owned and manufactured



Our Basic Troffer Wide (BTW LED) is now available in LED and has been developed utilising the latest technology, with a modern look and an ultra slim body with a maximum height of only 38mm for ease of installation in the smallest of ceiling cavities.


This fitting comes complete with a 100mm plexiglass frosted diffuser for perfect uniformity.

Can be configured to suit your requirements.

Part No	Power consumption (Watts)	CCT	CRI	COB Lumen	Lumen Flux	Lifetime L70b50	Size Length x width x height (mm)	Tee Bar (mm)	Weight (Mass)
BTW144LZ04AL830	29.5w	3000k	>80	4400lm	3850lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW144LZ04AL840	28w	4000k	>80	4400lm	3850lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW132LZ04AL830	21w	3000k	>80	3200lm	2800lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW132LZ04AL840	20w	4000k	>80	3200lm	2800lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW126LZ04AL830	17w	3000k	>80	2600lm	2300lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW126LZ04AL840	16.5w	4000k	>80	2600lm	2300lm	50,000h	1190 x 595 x 38	1200 x 600	6.0kg
BTW122LZ04AL830	15w	3000k	>80	2200lm	1900lm	50,000h	590 x 595 x 38	600 x 600	4.0kg
BTW122LZ04AL840	15w	4000k	>80	2200lm	1900lm	50,000h	590 x 595 x 38	600 x 600	4.0kg
BTW116LZ04AL830	11w	3000k	>80	1600lm	1400lm	50,000h	590 x 595 x 38	600 x 600	4.0kg
BTW116LZ04AL840	11w	4000k	>80	1600lm	1400lm	50,000h	590 x 595 x 38	600 x 600	4.0kg
BTW113LZ04AL830	9w	3000k	>80	1300lm	1150lm	50,000h	590 x 595 x 38	600 x 600	4.0kg
BTW113LZ04AL840	9w	4000k	>80	1300lm	1150lm	50,000h	590 x 595 x 38	600 x 600	4.0kg

Standard Features

0.7mm Zinc Anneal Steel Body
Powder coated white
Y5 Diffuser
Fits Metric T-Bars
5 Year warranty
(subject to standard terms and conditions)



Options

Colour temperature options (kelvin)
Dimming options
DALI addressable
Sensing options
Powder coating colour options
Plug & lead options
SR Automation
This fitting can be modified to order please contact our sales department for your requirements including imperial sizes

Compliance / Approvals

Input voltage 220-240 / 50Hz
AS60598
EMC (CISPR15)
C tick
SAA
IPART Acceptance No. 12422S15-VFG758

Website: www.harcroftlighting.com.au Phone:(02) 9624 7244 Fax: (02) 9624 7544 Email: sales@harcroftlighting.com.au

Disclaimer:

Whilst every care has been taken to ensure its accuracy, Harcroft Lighting will not accept responsibilities for any errors and omissions. Harcroft Lighting reserves the right to make changes from time to time without notice or obligation in specification, design, colour or materials including alterations to or discontinue models.